## NSN 5905-00-941-4479

**Section Quantity:** 

Cylindrical bushing mounted

Between 0.906 inches and 1.000 inches

Reliability Indicator:

Not established

Overall Length:

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-941-4479

| Body Diameter:  |
|---|
| Between 0.890 inches and 0.922 inches                     |
| Shaft Diameter:   |
| Between 0.248 inches and 0.251 inches                     |
| Shaft Length:   |
| 0.500 inches  |
| Mounting Bushing Length:                                  |
| 0.380 inches  |
| Body Length:  |
| Between 0.437 inches and 0.469 inches                     |
| Overall Diameter:   |
| 1.274 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Maximum Starting Torque:                                  |
| 6.00 inch-ounces  |
| Maximum Stop Torque:                                      |
| 128.00 inch-ounces  |
| Nonturn Device Location:                                  |
| At 9 oclock   |
| Nonturn Device Radius:                                    |
| 0.438 inches  |
| Screw Thread Diameter:                                    |
| 0.375 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
|   |
|   |

## NSN 5905-00-941-4479

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section:  |
|---|
| 250.0 ohms single section   |
| Rotary Actuator Travel In Angular Deg:  |
| Between 251.0 and 318.0   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:   |
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:  |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:  |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Test Data Document:   |
| 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Specification Data:   |
| 81349-mil-r-94/4 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A002a0