Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-941-9077

## Section Quantity:

1

# Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.375 inches and 1.405 inches **Body Diameter:** 0.750 inches

**Body Style:** 

Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.375 inches

#### **Overall Diameter:**

0.750 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

Between 340.0 and 350.0

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Rear end

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

5.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

360.0

## Power Dissipation Rating Per Section In Watts:

1.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 solder stud Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0