## NSN 5905-00-942-0158

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-942-0158 **Section Quantity: Body Style:** Cylindrical servo mounted **Pilot Diameter:** 1.87500 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 0.968 inches **Mounting Lip Diameter:** 2.00000 inches **Mounting Lip Depth:** 0.06200 inches **Mounting Hole/stud Circle Diameter:** 0.531 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Effective Electrical Rotation In Deg Angular Rotation:** 

**Actuator Type:** Single shaft 356.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces

## NSN 5905-00-942-0158

**Shaft End Play:** 

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.006 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring and threaded hole
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.50/+1.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Function Conformity Per Section:
Single section absolute conformity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees sine
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## NSN 5905-00-942-0158

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0