Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-942-3745

Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

Terminal Length:

1.000 inches

**Body Length:** 

0.234 inches

**Body Width:** 

0.312 inches

Body Height:

0.312 inches

Actuator Type:

## Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

280.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Terminal

**Electrical Resistance Per Section:** 

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

### **Power Dissipation Rating Per Section In Watts:**

0.6 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A002a0