Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-942-4974

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.088 inches

#### Shaft Diameter:

0.115 inches

Shaft Length:

0.062 inches

#### Body Length:

1.250 inches

### Body Width:

0.280 inches

# Body Height:

0.312 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9000.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

2

## Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

20.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

9000.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-10.0/+20.0 single section

### Actuator Travel Control Feature:

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0