NSN 5905-00-943-3863

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-943-3863

Ocation Oceantitus
Section Quantity:
Body Style:
Rectangular Patrability to the stage of the
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Length:
0.190 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
280.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-943-3863

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0