NSN 5905-00-943-3865

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-943-3865 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.202 inches **Body Length:** Between 0.495 inches and 0.505 inches **Body Width:** Between 0.185 inches and 0.195 inches **Body Height:** Between 0.525 inches and 0.535 inches **Shaft Bearing Type:** Sleeve **Actuator Type:** Recessed drive with slot **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Cubic Measure:** 0.052 cubic inches **Electrical Resistance Per Section:** 50.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal:

0.095 mils and 0.105 centimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

NSN 5905-00-943-3865

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: