Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-943-3865

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
Between 0.172 inches and 0.202 inches
Body Length:
Between 0.495 inches and 0.505 inches
Body Width:
Between 0.185 inches and 0.195 inches
Body Height:
Between 0.525 inches and 0.535 inches
Shaft Bearing Type:
Sleeve
Actuator Type:
Recessed drive with slot
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
Between 0.195 inches and 0.205 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Terminal
Cubic Measure:
0.052 cubic inches
Electrical Resistance Per Section:
50.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.095 mils and 0.105 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section

NSN 5905-00-943-3865

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0