

View Online at <https://aerobasegroup.com/nsn/5905-00-943-9087>

Section Quantity:

1

Body Style:

Rectangular w/bushing/slot mounted

Reliability Indicator:

Not established

Overall Length:

0.800 inches

Overall Height:

Between 0.548 inches and 0.568 inches

Overall Width:

Between 0.266 inches and 0.286 inches

Mounting Hole Diameter:

Between 0.070 inches and 0.076 inches

Shaft Diameter:

Between 0.088 inches and 0.098 inches

Shaft Length:

0.281 inches

Mounting Bushing Length:

0.281 inches

Body Length:

Between 0.540 inches and 0.560 inches

Body Width:

Between 0.266 inches and 0.286 inches

Body Height:

Between 0.548 inches and 0.568 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.513 inches and 0.526 inches

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Standard bushing and unthreaded hole

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0