## NSN 5905-00-944-0790

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-944-0790

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.205 inches
Body Diameter:
0.450 inches
Body Length:
0.235 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
280.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## NSN 5905-00-944-0790

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Special Features:
Screwdriver slot adjustment
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila

A002a0