NSN 5905-00-944-2028

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-944-2028 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.982 inches **Terminal Length:** 0.250 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** Between 0.962 inches and 1.002 inches **Overall Diameter:** 3.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 358.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.20 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Shaft End Play:** 0.005 inches

Shaft Runout: 0.0005 inches

NSN 5905-00-944-2028

Lateral Runout:

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



0.004 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.500 inches
Screw Thread Series Designator:
Un
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 solder stud

N/a

NSN 5905-00-944-2028

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0