## NSN 5905-00-944-2031

**Section Quantity:** 

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-944-2031

1.312 inches
Body Diameter:
Between 0.844 inches and 0.906 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.578 inches and 0.672 inches
Mounting Bushing Length:
Between 0.219 inches and 0.297 inches
Body Length:
Between 0.625 inches and 0.751 inches
Overall Diameter:
Between 0.984 inches and 1.141 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.250 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing

## NSN 5905-00-944-2031

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 290.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
12.5 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/1 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: