NSN 5905-00-944-3874

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-944-3874

Section Quantity:
1
Reliability Indicator:
Not established
Overall Length:
1.090 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Overall Diameter:
0.880 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1800.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.40 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section

NSN 5905-00-944-3874

Precision Wire Wound Variable Resistor - Page 2 of 2



Tan	Location	Tolerance	Per	Section:
ıap	LUCALIUII	i Olei alice	L 61	Section.

-2.0/+2.0 ohms single section

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0