## NSN 5905-00-944-7810

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-944-7810

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Overall Length:   |
| 0.875 inches  |
| Body Diameter:  |
| 0.656 inches  |
| Shaft Diameter:   |
| 0.125 inches  |
| Shaft Length:   |
| 0.375 inches  |
| Mounting Bushing Length:                                  |
| 0.250 inches  |
| Body Length:  |
| 0.500 inches  |
| Overall Diameter:   |
| 0.938 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Nonturn Device Location:                                  |
| At 9 oclock   |
| Nonturn Device Radius:                                    |
| 0.266 inches  |
| Screw Thread Diameter:                                    |
| 0.250 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Features Provided:  |
| Nonmetallic shaft   |

**Electrical Resistance Per Section:** 50.0 kilohms single section

## NSN 5905-00-944-7810

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



|  | Ambient Tempurature | In Deg | <b>Celsius Pe</b> | r Section | At Zero | Percent | Rated | Power: |
|--|---------------------|--------|-------------------|-----------|---------|---------|-------|--------|
|--|---------------------|--------|-------------------|-----------|---------|---------|-------|--------|

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

\_\_\_\_\_

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0