

View Online at <https://aerobasegroup.com/nsn/5905-00-944-9207>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.812 inches

**Body Diameter:**

1.818 centimeters

**Shaft Diameter:**

0.2497 inches

**Shaft Length:**

0.625 inches

**Body Length:**

2.187 inches

**Overall Diameter:**

2.406 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3601.0

**Maximum Starting Torque:**

1.30 inch-ounces

**Maximum Running Torque:**

0.90 inch-ounces

**Maximum Stop Torque:**

600.00 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.0005 inches

**Lateral Runout:**

0.0015 inches

**Pilot Diameter Runout:**

0.0001 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

50.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

3780.0

**Function Conformity Tolerance Per Section:**

-0.025/+0.025 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

7 oclock all primaries

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0