Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-944-9219

# Section Quantity:

1

# Body Style: Cylindrical bushing mounted

Reliability Indicator:

Not established

## **Overall Length:**

Between 2.720 inches and 2.810 inches

## First Flat Length:

0.344 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

2.810 inches

#### Shaft Diameter:

0.250 inches

# Shaft Length:

0.875 inches

# Mounting Bushing Length:

0.375 inches

# Body Length:

1.780 inches

#### **Overall Diameter:**

3.225 inches

# Shaft Style:

Round, flatted

# Contact Arm Electrical Off Position:

Fully cw

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

48.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

# Nonturn Device Radius:

0.500 inches

#### Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# NSN 5905-00-944-9219

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

**Electrical Resistance Per Section:** 

8.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 310.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

75.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/7 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0