

View Online at https://aerobasegroup.com/nsn/5905-00-944-9266

# Section Quantity:

1

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.5000 inches

#### **Pilot Length:**

0.0400 inches

#### **Undercut Diameter:**

1.875 inches

#### **Undercut Width:**

0.0620 inches

#### **Body Diameter:**

1.990 inches

# Shaft Diameter:

onan Diameter.

0.1249 inches

# Shaft Length:

0.500 inches

#### Body Length:

1.060 inches

#### Mounting Lip Diameter:

1.9900 inches

# Mounting Lip Depth:

0.1250 inches

#### Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

352.0

# Maximum Starting Torque:

1.00 inch-ounces

# Maximum Running Torque:

1.00 inch-ounces

# Shaft End Play:

0.006 inches

# Shaft Runout:

0.002 inches



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.35/+0.35 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0