NSN 5905-00-945-0328

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-0328

View Online at https://aerobasegroup.com/nsn/5905-00-945-0
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 0.490 inches and 0.510 inches
Terminal Length:
0.500 inches
Overall Height:
Between 0.710 inches and 0.730 inches
Overall Width:
Between 0.520 inches and 0.540 inches
Mounting Hole Diameter:
Between 0.075 inches and 0.081 inches
Shaft Diameter:
0.030 inches
Shaft Length:
0.083 inches
Body Length:
Between 0.510 inches and 0.530 inches
Body Width:
Between 0.490 inches and 0.510 inches
Body Height:
Between 0.210 inches and 0.230 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.190 inches and 0.210 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.490 inches and 0.510 inches
Mounting Facility Quantity:
2
Terminal Location:

Left adjacent side single row

NSN 5905-00-945-0328

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Mtg holes located diagonally opposite on plane formed by lg and w, pin-dia 0.028 in.
Terminal Type And Quantity:
3 pin
Reference Number Differentiating Characteristics:
As differentiated by navord od44548
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0