

View Online at <https://aerobasegroup.com/nsn/5905-00-945-0449>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8740 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

1.812 inches

Undercut Width:

0.0930 inches

Body Diameter:

1.812 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.625 inches

Body Length:

2.156 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

3680.0

Maximum Starting Torque:

1.30 inch-ounces

Maximum Running Torque:

0.90 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3680.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section absolute linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-2.0/+2.0 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 single section

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0