

View Online at <https://aerobasegroup.com/nsn/5905-00-945-2020>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Overall Length:

0.530 inches

Terminal Length:

0.500 inches

Overall Height:

0.500 inches

Overall Width:

0.720 inches

Mounting Hole Diameter:

Between 0.075 inches and 0.081 inches

Shaft Diameter:

0.083 inches

Shaft Length:

0.030 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

0.220 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.510 inches and 0.530 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side two rows

Mounting Method:

Unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Reference Number Differentiating Characteristics:

Navord od44548

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0