NSN 5905-00-945-3330

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-3330 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 1.000 inches **Terminal Length:** Between 0.490 inches and 0.510 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.210 inches and 0.230 inches **Mounting Hole Diameter:** Between 0.075 inches and 0.081 inches **Shaft Diameter:** 0.083 inches **Shaft Length:** Between 0.020 inches and 0.040 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.210 inches and 0.230 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals: Lateral Distance Between Mounting Hole Centers:** Between 0.510 inches and 0.530 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

Electrical Resistance Per Section:

20.0 kilohms single section

NSN 5905-00-945-3330

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-300.0/+300.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0