NSN 5905-00-945-5171

Section Quantity:

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-5171

Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.344 inches and 1.662 inches
Overall Height:
Between 0.437 inches and 0.469 inches
Overall Width:
0.375 inches
Mounting Hole Diameter:
Between 0.226 inches and 0.231 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.306 inches and 0.328 inches
Body Length:
Between 1.328 inches and 1.360 inches
Body Width:
0.375 inches
Body Height:
Between 0.437 inches and 0.469 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
Between 0.095 inches and 1.005 inches
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Standard bushing and unthreaded hole

NSN 5905-00-945-5171

Unit Of Measure:

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
15.0 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
90536-4912695 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a