Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-5274

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.578 inches

Overall Height:

0.391 inches

Overall Width:

0.359 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.250 inches

Body Length:

1.328 inches

Body Width:

0.359 inches

Body Height:

0.344 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.688 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Features Provided:

Nonmetallic shaft

NSN 5905-00-945-5274

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 20.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 7920.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.328 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -800.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Shaft all threaded **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0