NSN 5905-00-945-5381

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-945-5381 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.610 inches **Undercut Diameter:** 1.813 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 1.985 inches **Overall Diameter:** 2.250 inches **Mounting Lip Diameter:** 1.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:**

Ball

Actuator Type:

Single shaft

NSN 5905-00-945-5381

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation: 3600.0 **Maximum Starting Torque:** 1.20 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Maximum Stop Torque:** 1000.00 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.002 inches **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring and threaded hole **Electrical Resistance Per Section:** 100.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 8.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity

-3.0/+3.0 single section

Resistance Tolerance Per Section In Percent:

NSN 5905-00-945-5381

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0