

View Online at <https://aerobasegroup.com/nsn/5905-00-945-5381>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Overall Length:

2.610 inches

Undercut Diameter:

1.813 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

30.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.2497 inches

Shaft Length:

0.625 inches

Body Length:

1.985 inches

Overall Diameter:

2.250 inches

Mounting Lip Diameter:

1.8750 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.20 inch-ounces

Maximum Running Torque:

0.80 inch-ounces

Maximum Stop Torque:

1000.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.002 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring and threaded hole

Electrical Resistance Per Section:

100.000 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

8.0 7th secondary quality

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

7 oclock all primaries

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0