

View Online at <https://aerobasegroup.com/nsn/5905-00-945-5384>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

4.906 inches

Undercut Diameter:

Between 1.874 inches and 1.875 inches

Undercut Width:

0.0730 inches

Body Diameter:

2.031 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Body Length:

4.250 inches

Overall Diameter:

2.265 inches

Mounting Lip Diameter:

Between 1.9900 inches and 2.0050 inches

Mounting Lip Depth:

Between 0.0880 inches and 0.0980 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Fragility Factor:

Moderately delicate

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

80.0 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0