

View Online at <https://aerobasegroup.com/nsn/5905-00-945-6306>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.5610 inches and 1.5620 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.317 inches

**Undercut Diameter:**

0.562 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

1.750 inches

**Shaft Diameter:**

Between 0.249 inches and 0.250 inches

**Shaft Length:**

Between 0.688 inches and 0.750 inches

**Body Length:**

1.442 inches

**Overall Diameter:**

2.000 inches

**Mounting Lip Diameter:**

1.7500 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

354.0

**Maximum Starting Torque:**

1.10 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.15/+0.15 all sections

**Power Dissipation Rating Per Section In Watts:**

3.0 free air all sections

**Function Conformity Per Section:**

All sections absolute linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Test Data Document:**

10001-2325869 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0