NSN 5905-00-945-7151

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-7151

Section Quantity: Body Style: Cylindrical **Reliability Indicator:** Not established **Overall Length:** Between 0.709 inches and 0.771 inches **Terminal Length:** Between 0.484 inches and 0.516 inches **Body Diameter:** 0.500 inches **Body Length:** Between 0.195 inches and 0.225 inches **Overall Diameter:** 0.500 inches **Actuator Type:** Flush drive with slot-hole **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 20.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 100.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 285.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -400.0/+150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

NSN 5905-00-945-7151

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0