NSN 5905-00-945-9527

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-945-9527 **Section Quantity: Body Style:** Cylindrical friction mounted **Reliability Indicator:** Not established **Overall Length:** 2.875 inches **Body Diameter:** 1.875 inches **Shaft Diameter:** Between 0.2494 inches and 0.250 inches **Shaft Length:** Between 0.594 inches and 0.656 inches **Body Length:** 2.250 inches **Overall Diameter:** 2.375 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 1.20 inch-ounces **Maximum Stop Torque:** 1000.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Pilot Diameter Runout:** 0.002 inches **Shaft Radial Play:** 0.002 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:**

Nonmetallic shaft

NSN 5905-00-945-9527

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1805.0 single section
Rotary Actuator Travel In Angular Deg:
3610.0
Function Conformity Tolerance Per Section:
-0.09/+0.09 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-10.0/+10.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section graph
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
92220-r080-601-2043 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-

No

Fiig:

A002a0

Demilitarization: