## NSN 5905-00-946-4008

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-946-4008

Electrical Resistance: 1.100 kilohms Resistance Tolerance in Percent: 5.000/r4.5000 Ambient Tempurature In Deg Celsius At Full Rated Power: 18.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 18.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 18.00 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 18.00 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Rate Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Range Of Tempurature Coefficient in Deg Celsius: 18.00 Ambient Range Of Tempurature Rated Power: 18.00 Ambient Rated Power: 18.00 Ambient Range Of Tempurature Rated Power: 18.00 Ambient Rated Power: 1	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.0004-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 55.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 56.04-350.0 Tempurature Range Of Tempurature Ra	-260.0/+260.0
Resistance Tolerance in Percent: 5.000/+5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 5.00 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 5.00 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 5.00.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 5.5.0/+3.5.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: All designation Rating In Watts: 10.344 inches 30-dy Langth: 8.875 inches Power Dissipation Rating In Watts: 10.1000 free air Style Designator: Availaterminal each end Test Data Document: 194349-milr 26/44 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 194349-milr 26/44 specification, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Joint Of Measure: Joint Of	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4350.0 Inclosure Method: 25.0/4350.0 Inclosure Method: 25.0/200 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4350.0 Inclosure Method: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rated Power: 25.0/200 Rempurature In Deg Celsius At Zero Percent Rate	9.100 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Coefficient In Deg Celsius:  25.0  Empurature Range Of Tempurature Range Of Tempuratu	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0  100.0  1	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  15.0/4350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  1.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  11.149-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa Juit Of Measure:  Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wife lead  Reliability Indicator:  Not established  Body Diameter:  3.344 inches  3ody Length:  8.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Ryle Designator:  Avial terminal each end  Fest Data Document:  11349-milr 26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Juit Of Measure:  Demilitarization:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  3.344 inches  3.340 Length:  8.75 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  kixial terminal each end  Test Data Document:  81349-milit26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  boxcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Value  Unit Of Measure:  Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 3.344 inches 3.364y Length: 3.875 inches Power Dissipation Rating in Watts: 11.000 free air Style Designator: Xixial terminal each end Fest Data Document: 31349-milit26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; xixcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure:	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter:344 inches 30dy Length:875 inches Power Dissipation Rating in Watts: 11.000 free air Style Designator: xical terminal each end Fest Data Document: 11.349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  Va Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.344 inches Body Length: 8.875 inches Power Dissipation Rating In Watts: 11.000 free air Skyle Designator: Natial terminal each end Fest Data Document: 131349-miliz 6/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  1/4  1/4  1/5  1/6  1/6  1/7  1/7  1/8  1/8  1/8  1/8  1/8  1/8	-55.0/+350.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Va  Juit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Notes Reliability Indicator: N	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.344 inches  Body Length: 1.875 inches  Power Dissipation Rating In Watts: 11.000 free air  Style Designator: Axial terminal each end  Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure: - Demilitarization:	Terminal Type:
Note established  Body Diameter:  Dia44 inches  Body Length:  L875 inches  Power Dissipation Rating In Watts:  11.000 free air  Byle Designator:  Avail terminal each end  Fest Data Document:  Bra49-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Byle Directory Commercial Catalogs of the conditions of the condi	Wire lead
Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Reliability Indicator:
3.344 inches 3.60dy Length:  1.875 inches 2.60wer Dissipation Rating In Watts:  1.1.000 free air 3.6xyle Designator:  Axial terminal each end 1.6st Data Document:  3.1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;  3.6xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  3.6xcludes Commercial Catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  3.6xcludes Commercial Catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  3.6xcludes Commercial Catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Not established
Body Length:  1.875 inches  Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts:  11.000 free air  Style Designator: Axial terminal each end  Test Data Document:  31.349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	0.344 inches
Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Length:
1.000 free air  Style Designator: Axial terminal each end  Fest Data Document: B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.875 inches
Axial terminal each end  Fest Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	11.000 free air
Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Style Designator:
B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a  Unit Of Measure: Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:  - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
iig:	No
	Fiig:
4001a0	A001a0