Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-946-4055

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Body Diameter:**

2.000 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.313 inches

#### Body Length:

0.720 inches

#### Shaft Style:

Round

# Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.50 inch-ounces

#### Maximum Running Torque:

0.50 inch-ounces

# Maximum Stop Torque:

0.50 inch-ounces

#### Nonturn Device Location:

At 3 oclock

#### **Nonturn Device Radius:**

0.490 inches

#### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.002 inches

# Lateral Runout:

0.002 inches

### **Pilot Diameter Runout:**

0.0015 inches



# **Shaft Radial Play:** 0.002 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

# NSN 5905-00-946-4055

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

