## NSN 5905-00-946-7320

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-946-7320

Electrical Resistance: 73.200 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 0.812 inches
73.200 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Hermetically sealed  Teminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length:
Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+125.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter:  0.312 inches  Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+125.0  Inclosure Method:  Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.312 inches  Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
-55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length:
Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter:  0.312 inches  Body Length:
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter:  0.312 inches  Body Length:
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.312 inches  Body Length:
Reliability Indicator: Not established  Body Diameter:  0.312 inches  Body Length:
Not established  Body Diameter:  0.312 inches  Body Length:
Body Diameter:  0.312 inches  Body Length:
0.312 inches  Body Length:
Body Length:
0.812 inches
Power Dissipation Rating In Watts:
0.500 free air
Criticality Code Justification:
Test
Style Designator:
Axial terminal each end
Test Data Document:
04655-36-268717-7329 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer
drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0