

View Online at https://aerobasegroup.com/nsn/5905-00-946-7933

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

4.641 inches

Undercut Diameter:

Between 1.874 inches and 1.875 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

Between 0.609 inches and 0.641 inches

Body Length:

4.000 inches

Overall Diameter:

2.116 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7380.0

Maximum Starting Torque:

1.30 inch-ounces

Maximum Running Torque:

0.90 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces



Terminal Location: Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 6.25 kilohms single section **Rotary Actuator Travel In Angular Deg:** 7380.0 **Function Conformity Tolerance Per Section:** -0.45/+0.45 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section absolute linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -5.0/+5.0 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Tap Location From Ccw Terminal Per Section In Ohms: 2500.0 single section **Function Characteristic Per Section:** Single section linear **Test Data Document:** 10001-2325870 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0