NSN 5905-00-947-4382

A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-947-4382

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: -2.0.0/+2.0.0 Electrical Resistance: 17.800 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -85.0/+145.0 Inclosure Method: Encapsulated Terminal Type: -3ab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Sover Dissipation Rating in Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data:
Electrical Resistance: 17.800 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -45.0/+145.0 Inclosure Method: Encapsulated Terminal Type: -13b, solder lug Reliability Indicator: Not estabilished Terminal Length: 0.376 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Fower Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81494-mil-P3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Resistance Tolerance in Percent: -1,000/4+1,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65,0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Solder lug Reliability Indicator: Not ostablished Terminal Length: 0.500 inches Solder Length: 0.500 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Designator Rating in Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-793 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: -7ab, solder lug Reliability Indicator: Not established Terminal Length: -0.375 inches Body Diameter: -0.500 inches Body Diameter: -0.500 inches Body Length: -0.500 inches Solder lug Reliability Indicator: Rose of Dissipation Rating in Watts: -0.500 inches Solder lug Reliability Indicator: Rose of Dissipation Rating in Watts: -0.500 inches Roder Dissipation Rating in Watts: -0.500 inches Rower Dissipation Rating in Watts
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Encapsulated Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating in Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 0.50
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
-65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Not established Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Length: 0.375 inches Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Body Diameter: 0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
0.500 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Power Dissipation Rating In Watts: 0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
0.250 free air Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Width: 0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
0.188 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Radial terminal each end Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Test Data Document: 81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
81349-mil-r-93/15 government specification
Shelf Life:
N/a
Unit Of Measure:
••
Demilitarization:
Demilitarization: No