NSN 5905-00-948-1510

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-948-1510

Section Quantity:
1
Shaft Diameter:
0.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
1080.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug

NSN 5905-00-948-1510

Precision Wire Wound Variable Resistor - Page 2 of 2



Shelf L	ife:
N/a	
Unit Of	Me

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0