

View Online at https://aerobasegroup.com/nsn/5905-00-948-2585

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.813 inches

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.2497 inches

#### Shaft Length:

0.813 inches

#### Mounting Bushing Length:

# 0.313 inches

**Body Length:** 

1.000 inches

#### **Overall Diameter:**

1.063 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.60 inch-ounces

#### Maximum Running Torque:

0.60 inch-ounces

#### Maximum Stop Torque:

96.00 inch-ounces

#### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.002 inches

#### Lateral Runout:

0.005 inches

#### **Pilot Diameter Runout:**

0.002 inches

#### Shaft Radial Play:

0.003 inches



# **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof and shaft seal **Electrical Resistance Per Section:** 5.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.20/+0.20 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0