NSN 5905-00-948-8439

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-948-8439

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
4.457 inches
First Flat Length:
1.500 inches
Flat Height:
0.344 inches
Body Diameter:
6.090 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.500 inches
Body Length:
2.410 inches
Overall Diameter:
6.810 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Maximum Starting Torque:
160.00 inch-ounces
Maximum Stop Torque:
240.00 inch-ounces
Nonturn Device Location:
At 3 oclock and at 9 oclock
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:

NSN 5905-00-948-8439

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
350.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 310.0 and 325.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
390.0 single section
Power Dissipation Rating Per Section In Watts:
300.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Two mtg holes spaced 180 degrees on 1.190 in. Radius
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/11 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No