

View Online at <https://aerobasegroup.com/nsn/5905-00-948-8672>

**Section Quantity:**

4

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.750 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

2.420 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

291.0

**Maximum Starting Torque:**

4.50 inch-ounces

**Maximum Running Torque:**

4.00 inch-ounces

**Maximum Stop Torque:**

128.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Shaft End Play:**

0.015 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.0015 inches

**Shaft Radial Play:**

0.002 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

50.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

291.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-200.0/+200.0 all sections

**Power Dissipation Rating Per Section In Watts:**

3.0 heat sink all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0