## NSN 5905-00-948-8823

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-948-8823 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.281 inches **Shaft Length:** 0.688 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.457 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

145.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

## NSN 5905-00-948-8823

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent:                        |
|---|
| -2.0/+2.0 single section  |
| Actuator Travel Control Feature:                                    |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section   |
| Standard Taper Curve Per Section:                                   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 turret  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |