## NSN 5905-00-948-9389

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-948-9389 **Section Quantity: Overall Length:** 1.521 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.250 inches **Overall Diameter:** 0.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 75.000 kilohms single section **Function Conformity Tolerance Per Section:** -0.025/+0.025 single section **Power Dissipation Rating Per Section In Watts:** 

1.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section

## NSN 5905-00-948-9389

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity
----------------------------

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0