NSN 5905-00-949-0238

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-949-0238 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.060 inches **Terminal Length:** 0.200 inches **Overall Height:** 0.560 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.060 inches **Body Length:** 1.000 inches **Body Width:** 0.280 inches **Body Height:** 0.280 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** 0.050 inches **Lateral Distance Between Mounting Hole Centers:** 0.830 inches **Mounting Facility Quantity:**

2 **Terminal Location:** Rear-bottom **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 5400.0

NSN 5905-00-949-0238

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: 0.200 inches

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0