NSN 5905-00-949-0820

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



949-0820

| View Online at https://aerobasegroup.com/nsn/5905-00- |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Rectangular w/mounting holes |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 0.530 inches |
| Terminal Length: |
| Between 0.172 inches and 0.202 inches |
| Overall Height: |
| Between 0.484 inches and 0.516 inches |
| Overall Width: |
| 0.442 inches |
| Mounting Hole Diameter: |
| Between 0.070 inches and 0.076 inches |
| Shaft Diameter: |
| Between 0.058 inches and 0.062 inches |
| Shaft Length: |
| 0.030 inches |
| Body Length: |
| Between 0.484 inches and 0.516 inches |
| Body Width: |
| Between 0.250 inches and 0.265 inches |
| Body Height: |
| Between 0.484 inches and 0.516 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Maximum Starting Torque: |
| 7.50 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Lateral Distance Between Mounting Hole Centers: |
| Between 0.515 inches and 0.530 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Left adjacent side single row |
| Mounting Method: |

Unthreaded hole

NSN 5905-00-949-0820

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|--|
| 1.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 16200.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.095 inches and 0.105 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power |
| 200.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0/+50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 50.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |