## NSN 5905-00-949-0820

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



949-0820

View Online at https://aerobasegroup.com/nsn/5905-00-
Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.530 inches
Terminal Length:
Between 0.172 inches and 0.202 inches
Overall Height:
Between 0.484 inches and 0.516 inches
Overall Width:
0.442 inches
Mounting Hole Diameter:
Between 0.070 inches and 0.076 inches
Shaft Diameter:
Between 0.058 inches and 0.062 inches
Shaft Length:
0.030 inches
Body Length:
Between 0.484 inches and 0.516 inches
Body Width:
Between 0.250 inches and 0.265 inches
Body Height:
Between 0.484 inches and 0.516 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
7.50 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.515 inches and 0.530 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side single row
Mounting Method:

Unthreaded hole

## NSN 5905-00-949-0820

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
16200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.095 inches and 0.105 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
200.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0