NSN 5905-00-949-2094

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-949-2094

Electrical Resistance: 365.000 ohms Resistance Tolerance In Percent: 2-0.000+2-0.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 2-5.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 2-5.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 2-5.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 385.000 ohms Resistance Tolerance In Percent: 2.000/42.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating in Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure:	
Resistance Tolerance In Percent: -2.0004-2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -235.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -45.04-235.0 Inclosure Method:	
Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: -Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r11804 specification (includes engineering type bullelins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r11804/1 government specification Sheft Life: Nia Unit Of Measure:	
Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 235.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04/255.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diamete: 0.500 inches Body Diamete: 0.500 inches Body Diamete: 0.500 inches Fower Dissipation Rating in Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Sheft Life: N/a Unit of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 fee air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil+-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical'', "average', ", etc.). Specification Data: 81349-mil+-11804/1 government specification Sheff Life: N/a Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: Tab. solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating in Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: Bal349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Bl349-mil-r-11804/1 government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 235.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating in Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mili-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mili-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-225.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+235.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-milr-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-11804/1 government specification Shelf Life: Na Unit Of Measure: Demilitarization:	
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Encapsulated Terminal Type: Tab., solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 fee air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: Na Unit Of Measure:	
Encapsulated Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-11804/1 government specification Shelf Life: N/a Unit Of Measure:	
Terminal Type: Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.501 inches Style Designator: Radial terminal each end Test Data Document: 81349-mill-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tab, solder lug Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Terminal Length: 0.531 inches Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	-
Body Diameter: 0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	-
0.500 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Body Length: 1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
1.500 inches Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Power Dissipation Rating In Watts: 7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
7.000 free air Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Terminal Width: 0.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
O.250 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure:	
Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Radial terminal each end Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Test Data Document: 81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
81349-mil-r-11804 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Specification Data: 81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
81349-mil-r-11804/1 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	
 Demilitarization:	
	Demilitarization:
Fiig:	