

View Online at <https://aerobasegroup.com/nsn/5905-00-949-2211>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.4675 inches

Pilot Length:

0.0620 inches

Overall Length:

3.241 inches

First Flat Length:

0.250 inches

Flat Height:

0.125 inches

Undercut Diameter:

1.468 inches

Undercut Width:

0.0780 inches

Body Diameter:

1.656 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.320 inches

Body Length:

1.890 inches

Overall Diameter:

2.153 inches

Mounting Lip Diameter:

1.6560 inches

Mounting Lip Depth:

0.0920 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

2.5 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary at 10'30 oclock

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

6 oclock all primaries

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0