Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-949-3409

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

### Terminal Length:

0.170 inches

#### Mounting Hole Diameter:

0.086 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.050 inches

#### Body Length:

1.000 inches

### Body Width:

0.180 inches

# Body Height:

0.300 inches

# Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

5400.0

### Center To Center Distance Between Terminals:

0.200 inches

### Lateral Distance Between Mounting Hole Centers:

0.750 inches

### Mounting Facility Quantity:

2

## Terminal Location:

Rear end

## Mounting Method:

Unthreaded hole

## **Electrical Resistance Per Section:**

50.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

5400.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

### **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0