NSN 5905-00-949-4686

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-949-4686

Toward and the state of Post Association and Post Post Post Post Post Post Post Post
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0
Electrical Resistance:
270.000 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.563 inches
Body Diameter:
1.312 inches
Body Length:
6.000 inches
Power Dissipation Rating In Watts:
113.000 free air
Terminal Width:
0.328 inches
Cubic Measure (non-core):
8.112 cubic inches
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-949-4686

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0