## NSN 5905-00-949-7817

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-949-7817

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.520 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.060 inches
Body Length:
0.571 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:

Continuous motion

## NSN 5905-00-949-7817

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg	Celsius Per Section	At Full Rated Power:
----------------------------	---------------------	----------------------

70.0 single section

**Terminal Type And Quantity:** 

3 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0