## NSN 5905-00-949-9998

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-949-9998

One them Overation
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.093 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.562 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
25.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:

1 single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## NSN 5905-00-949-9998

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tan	Location	From	CCW	<b>Terminal</b>	Dor	Section	In	Ohme
ıab	Location	LIOIII	CCW	rerminai	Per	Section	m	Onins.

12500.0 single section and 12500.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

4 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0