

View Online at <https://aerobasegroup.com/nsn/5905-00-949-9998>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.093 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.562 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

25.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Fixed Tap Quantity Per Section:**

1 single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Tap Location From Ccw Terminal Per Section In Ohms:**

12500.0 single section and 12500.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0